





Ford - Castrol Magnatec 0W-20

CLINGING MOLECULES PROTECT FROM THE START

Description

Up to 75% of engine wear happens while your engine warms up. When the engine stops oils drain off critical engine parts, however Ford - Castrol MAGNATEC's intelligent molecules don't. They cling to the engine like a magnet providing an extra layer of protection.

Ford - Castrol MAGNATEC's formulation protects from the moment you turn the key, dramatically reducing* engine wear. Ford - Castrol MAGNATEC. Instant protection from the moment you turn the key.

*As tested in the industry API SN Sequence IVA wear test.

Application

Ford - Castrol MAGNATEC 0W-20 is suitable for use in vehicles that require a 0W-20 lubricant that Meets Ford WSS-M2C954-A1 specification

Typical Characteristics

Name	Method	Units	Ford - Castrol Magnatec 0W-20
Density @ 15C, Relative	ASTM D1298	g/ml	0.841
Viscosity, Kinematic 100C	ASTM D445	mm²/s	8.3
Viscosity, CCS -35C (0W)	ASTM D5293	mPa.s (cP)	4405
Viscosity, Kinematic 40C	ASTM D445	mm²/s	43
Viscosity Index	ASTM D2270	None	177
Pour Point	ASTM D97	°C	-36
Flash Point, PMCC	ASTM D93	°C	202
Ash, Sulphated	ASTM D874	% wt	0.78

Product Performance Claims

Meets Ford WSS-M2C954-A1

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Ford - Castrol Magnatec 0W-20

17 Jul 2023

Castrol, Magnatec and related marks are trade marks of Castrol Ltd., used under licence. Ford is a trade mark of Ford Motor Company, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com