

DEF Anti Crystal Additive Concentrate



Description

Ash-free combination of additives for the prevention of malfunctions in the SCR system of diesel engines. Reduces the formation of deposits in the AdBlue® tank and AdBlue® injection system. Guarantees extremely fine atomization of the urea solution by lowering the surface tension. Optimizes the return flow of the AdBlue® into the system, thereby minimizing the risk of AdBlue® crystallization.

Technical data

Base	tenside, improves freezing point
Color / appearance	clear, colourless
Density at 15 °C	1,042 g/ml
Refractive index at 20 °C	1,427
Form	liquid
Odor	characteristic

Areas of application

For all SCR systems that are operated with 32.5 % urea solution (AdBlue®, DEF).

Comment

Frost sensitive. Shake at room temperature to disperse deposits on bottom!

Application

Add 0.25 % to the AdBlue® solution (1:400). 25 ml is sufficient for 10 l of AdBlue®. 250 ml is sufficient for 100 l of AdBlue®. 2.5 l is sufficient for 1000 l of AdBlue®. For long-term application. Do not add to fuel! When adding to the AdBlue® tank, should ideally be added after the filling process.

Available pack sizes

250 ml Dispensing bottle plastic	21799 GB-F-D-I-NL-ARAB- DK-S-FIN-N
250 ml Dispensing bottle plastic	21838 E-P-H-RO-TR-GR-RUS- PL-CZ
2,5 l Canister plastic	21800 D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.